



**CM12 - Bullet Camera Color Pole/Gooseneck Camera- MUST USE 5V DC!!!!**

<b>Optical Technology Base:</b>	COLOR 1/4" CCD
<b>Picture Elements (Horz x Vert in mm):</b>	EIA/NTSC: 510H x 492V - CCIR/PAL: 500H x 582V
<b>Resolution:</b>	380 Lines
<b>Minimun Illumination:</b>	1 Lux
<b>Horizontal Sync. Frequency:</b>	EIA/NTSC 15.734Khz & CCIR/PAL 15.625Khz
<b>Vertical Frequency :</b>	EIA/NTSC 60Hz & CCIR/PAL 50Hz
<b>Scanning:</b>	2:1 Interlace
<b>S/N Ratio:</b>	52 dB
<b>Electronic Shutter:</b>	1/120.000 / Sec Linear
<b>Lens:</b>	Pin Hole 3.7mm f2.0
<b>Gamma :</b>	0.45
<b>White Balance :</b>	Auto Tracing
<b>Video Output :</b>	1V p-p, 75 ohms
<b>Power Supply :</b>	5.0V
<b>Power Consumption :</b>	270mA / 12VDC (+/- 5.0V)
<b>Dimensions mm :</b>	16 x 274.5mm
<b>Weight :</b>	85g
<b>Storage Temperature:</b>	-30°C to +60°C

\* Pictures and specifications are subject to change without prior notice