



CM15L - Bullet Camera Color CCD with GOOSENECK Long Bracket 50 cm

|  |   |
|--|---|
| <b>Optical Technology Base:</b>              | COLOR 1/4" CCD                                |
| <b>Picture Elements (Horz x Vert in mm):</b> | EIA/NTSC: 510H x 492V - CCIR/PAL: 500H x 582V |
| <b>Resolution:</b>                           | 380 Lines                                     |
| <b>Minimun Illumination:</b>                 | 1 Lux   |
| <b>Horizontal Sync. Frequency:</b>           | EIA/NTSC 15.734Khz & CCIR/PAL 15.625Khz       |
| <b>Clock Frequency:</b>                      | EIA/NTSC 19.0699Mhz & CCIR/PAL 18.9375Mhz     |
| <b>Vertical Frequency :</b>                  | EIA/NTSC 60Hz & CCIR/PAL 50Hz                 |
| <b>Scanning:</b>                             | 2:1 Interlace                                 |
| <b>S/N Ratio:</b>                            | 52 dB   |
| <b>Electronic Shutter:</b>                   | 1/120.000 / Sec Linear                        |
| <b>Lens:</b>                                 | Pin Hole 3.6mm f2.0                           |
| <b>Gamma :</b>                               | 0.45  |
| <b>White Balance :</b>                       | Auto Tracing                                  |
| <b>Video Output :</b>                        | 1V p-p, 75 ohms                               |
| <b>Power Supply :</b>                        | 12V DC  |
| <b>Power Consumption :</b>                   | 110mA / 12VDC                                 |
| <b>Dimensions mm :</b>                       | Ø22 x 580mm                                   |
| <b>Weight :</b>                              | 100g  |
| <b>Storage Temperature:</b>                  | -30°C to +60°C                                |

\* Pictures and specifications are subject to change without prior notice

