



ASH65NV - Outdoor PTZ Night & Day Camera 216X Zoom

Image Sensor:	1/4" Super HAD CCD
Active Pixels:	752H x 582V
Synchronization:	Internal
Video Output:	VBS 1.0Vp-p /75 ohms
White Balance:	Auto/Manual
Scanning Frequency:	15625Khz (H) x 50Hz (V)
Resolution:	More than 480 Lines
S/N Ratio:	More than 46dB
Electronic Shutter:	1/50~1/30000s
Lux:	0.1 Lux
Lens Focal Length:	f=3.9~63mm
Zoom:	216X (18X Optical 12X Digital)
Tilt Speed:	0~40°/s
Pan Rotation:	360°
Tilt Rotation:	90° (180° Auto Overturn)
Preset:	64
Control Way:	Multiprotocol , RS485
Relative Humidity:	10-75%
Work Temperature:	-45°C~55°C
Power Source:	DC15VA± 10%, 1.5A , External
Power Consumption:	15VA
Weight:	2Kg

* Pictures and specifications are subject to change without prior notice

ASH65NV - Outdoor PTZ Night & Day Camera 270X Zoom

Image Sensor:	1/4" Super HAD CCD
Active Pixels:	752H x 582V
Synchronization:	Internal
Video Output:	VBS 1.0Vp-p /75 ohms
White Balance:	Auto/Manual
Scanning Frequency:	15625Khz (H) x 50Hz (V)
Resolution:	More than 480 Lines
S/N Ratio:	More than 50dB
Electronic Shutter:	1/50~1/30000s
Lux:	0.1 Lux
Lens Focal Length:	f=3.9~63mm
Zoom:	270X (27X Optical 10X Digital)
Tilt Speed:	0~40°/s
Pan Rotation:	360°
Tilt Rotation:	90° (180° Auto Overturn)
Preset:	64
Control Way:	Multiprotocol , RS485
Relative Humidity:	10-75%
Work Temperature:	-45°C~55°C
Power Source:	DC15VA± 10%, 1.5A , External
Power Consumption:	15VA
Weight:	2Kg

* Pictures and specifications are subject to change without prior notice