

Product Features :

- 6" Outdoor Ceiling/Wall Mount Speed Color Dome
- Day & Night Sony Super CCD
- Low Noise Design
- 360° Panning and 90° Tilt.
- Multiprotocol, RS485
- AC24V



Video :

27X

Optical Technology Base:
 Picture Elements (H x V in mm):
 Resolution:
 Mini Illumination:
 S/N Ratio:
 Zoom:
 Gain Control
 BLC
 Iris:
 White Balance:
 Signal Format:
 Video Output:

1/4" SONY Super CCD
 795(H) x 596(V) / - (PAL) / 811 x 508 (NTSC)
 480 Lines
 0.001 Lux F1.2 (Day&Night)
 >60dB
 27X Optical f=3.2 ~ 86.4mm
 Auto / Manual
 Auto / Manual
 Auto / Manual
 Auto / Manual
 Auto / Manual
 1±0.2Vp-p

PTZ:

Pan Speed: 0~15°/sec
 Tilt Speed: 0~15°/sec
 Pan Range: 360° continuously
 Tilt Range: 90°
 Presets: 64 presets (Total)
 Auto pan Scan: Programmable
 Communication: RS485 , Baudrate (2400/4800/9600/19200bps)
 Weight: 8Lbs / 4Kg
 Operating Temperature: -35°C to +55°C (w/ Housing)

Power:

Power Supply: AC24V 50/60hz
 Consumption: 10W (indoor)
 35W (outdoor)

Power Consumption

Motor Running: 600mA
 Standby: 370mA
 Fan Running: 450mA
 Heater on: 180mA

