



## FS35 - Fire Sprinkler Camera

|                                    |   |
|------------------------------------|---|
| <b>Image Sensor:</b>               | 1/4" SONY CCD                                     |
| <b>Picture elements :</b>          | EIA/NTSC: 512 H x 492 V - CCIR/PAL: 512 H x 582 V |
| <b>Horizontal resolution:</b>      | 420 TVL   |
| <b>Minimun Illumination:</b>       | 0.1 Lux   |
| <b>Horizontal Sync. frequency:</b> | EIA/NTSC: 15.734 KHZ - CCIR/PAL: 15.625 KHZ       |
| <b>Vertical frequency :</b>        | EIA/NTSC: 60 HZ - CCIR/PAL: 50 HZ                 |
| <b>Clock frequency:</b>            | EIA/NTSC: 19.0699 MHZ - CCIR/PAL: 18.9375 MHZ     |
| <b>Lens:</b>                       | Pinhole Lens 3.7mm                                |
| <b>Video output:</b>               | 1Vp-p , 75 Ohms                                   |
| <b>Gamma:</b>                      | 0.45  |
| <b>Power supply :</b>              | DC12V   |
| <b>Power Consumption:</b>          | 150 mA  |
| <b>Storage Temperature :</b>       | -30°C ~ 60°C                                      |
| <b>Operation Temperature :</b>     | -10°C ~ 45°C                                      |

\* Pictures and specifications are subject to change without prior notice