

SD35

- Covert Smoke Detector
- CCD Color Camera
- Pinhole 3.7mm Cone Shape Lens
- DC12V / 120mA



SPECIFICATIONS

MODEL	SD-35
Image Sensor	1/3" SONY CCD
Signal System	PAL/NTSC
Sensing area	4.9mm x 3.7mm
Effective Pixels	PAL:500(H) x 582(V) NTSC:510(H) x 492(V)
Scanning Frequency	PAL:15.625KHz(H) 50Hz(V) NTSC:15.7343KHz(H) 60Hz(V)
Horizontal Resolution	420TVL
Built-in Lens	4mm or 6mm/F1.5
Electronic Shutter	1/50(1/60)-1/100,000(sec)
S/N Ratio	More than 48dB(AGC OFF)
Minimum Illumination	1 Lux
White Balance	Auto tracking white balance
Infrared Lamps wavelength	850nm
Infrared Lamps Irradiation Distance	25m
Infrared Lamps	Day / Night ON/OFF
Back Light Compensation	ON/OFF Switchable
Auto Gain Control	ON/OFF Switchable
Electronic Shutter Control	EE/AI Switchable
Video Output	1.0Vp-p75Ω BNC
Grade of waterproof	IP x 5
Power Requirement	DC12V / 120mA
Power Consumption	About 1.5W
Dimensions	∅55mm x 108mm